



COVE 1 - LED BAR



Housing

Matt natural anodized, aluminum extrusion profile and mounting accessories with plastic end cap.

Optics

Opal, white, diffusing polycarbonate lens with lambertian light distribution.

Led

High-efficacy mid power LED with CRI>80, achieving L70B50 ≥ 50,000 hours of lifetime.

Driver

24Vdc external type. Constant voltage output driver with high efficiency.

Type	Type Code	CCT(K)	Light Output (lm)	CRI	Power (w)	V/Hz	L (mm)	Weight
SD 0135 CVI	SDCVI.135.2.30	3000	115	Ra>80	2	24V DC	135 mm	0,04 kg
	SDCVI.135.2.40	4000	125	Ra>80	2	24V DC	135 mm	0,04 kg
SD 0260 CVI	SDCVI.260.4.30	3000	240	Ra>80	4	24V DC	260 mm	0,07 kg
	SDCVI.260.4.40	4000	255	Ra>80	4	24V DC	260 mm	0,07 kg
SD 0505 CVI	SDCVI.505.8.30	3000	490	Ra>80	8	24V DC	505 mm	0,14 kg
	SDCVI.505.8.40	4000	520	Ra>80	8	24V DC	505 mm	0,14 kg
SD 1000 CVI	SDCVI.1000.16.30	3000	980	Ra>80	16	24V DC	1000 mm	0,28 kg
	SDCVI.1000.16.40	4000	1040	Ra>80	16	24V DC	1000 mm	0,28 kg
SD 1245 CVI	SDCVI.1245.20.30	3000	1220	Ra>80	20	24V DC	1245 mm	0,34 kg
	SDCVI.1245.20.40	4000	1290	Ra>80	20	24V DC	1245 mm	0,34 kg
SD 1495 CVI	SDCVI.1495.24.30	3000	1470	Ra>80	24	24V DC	1495 mm	0,41 kg
	SDCVI.1495.24.40	4000	1550	Ra>80	24	24V DC	1495 mm	0,41 kg

