Strio-LL Opal



Housing
Matt natural anodized, aluminum extrusion profile and mounting accessories with plastic end cap

Diffuser
Opal, white, diffusing polycarbonate diffuser with lambertian light distribution

Led
High-efficacy mid power LED, achieving L70B50 ≥ 50,000 hours of lifetime

Driver
24V external type. Constant voltage output driver with high efficiency

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)
SDSRL0140.1,5.40	1,5	4000	133	>80	24V DC	140
SDSRL0140.1,5.30	1,5	3000	130	>80	24V DC	140
SDSRL.0264.3.40	3	4000	268	>80	24V DC	264
SDSRL.0264.3.30	3	3000	262	>80	24V DC	264
SDSRL.0511.7.40	7	4000	535	>80	24V DC	511
SDSRL.0511.7.30	7	3000	524	>80	24V DC	511
SDSRL.1005.13.40	13	4000	1088	>80	24V DC	1005
SDSRL.1005.13.30	13	3000	1066	>80	24V DC	1055
SDSRL.1252.16.40	16	4000	1389	>80	24V DC	1252
SDSRL.1252.16.30	16	3000	1361	>80	24V DC	1252
SDSRL.1499.20.40	20	4000	1694	>80	24V DC	1499
SDSRL.1499.20.30	20	3000	1660	>80	24V DC	1499


105°
105°
90°
90°
75°
75°
60°
60°
200
45°
45°
300
400
30°
15°
0°
15°
30°
cd/klm
C0 - C180
C90 - C270
η = 100%

L
7,3
18
12,7