




PLUS-U



Housing

Matte natural anodized, aluminum extrusion profile and stainless steel mounting accessories with plastic ceiling cup.

Optics

Opal, white, diffusing polycarbonate lens with lambertian light distribution.

Led

High-efficacy mid power LED with CRI>80, achieving L90B50 \geq 50,000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and $Pf \geq 0.95$

Options

Dimming via DALI

Color

Matte natural anodized

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)
SPLU.1500.44.30	44	3000	3970	>80	220 - 240 / 50 - 60	3,4
SPLU.1500.44.40	44	4000	4230	>80	220 - 240 / 50 - 60	3,4
SPLU.1800.54.30	54	3000	4680	>80	220 - 240 / 50 - 60	3,7
SPLU.1800.54.40	54	4000	4980	>80	220 - 240 / 50 - 60	3,7
SDPLU.1500.44.30	44	3000	3970	>80	220 - 240 / 50 - 60	3,16
SDPLU.1500.44.40	44	4000	4230	>80	220 - 240 / 50 - 60	3,16
SDPLU.1800.54.30	54	3000	4680	>80	220 - 240 / 50 - 60	3,46
SDPLU.1800.54.40	54	4000	4980	>80	220 - 240 / 50 - 60	3,46

