



DG 1020 MON+



Housing

Aluminum injection frame with electrostatic powder coating and die-cast aluminum heatsink.

Optics Opal white polystyrene diffuser with lambertian light distribution.


Led High-efficacy LED module with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

Driver Constant current output LED driver with high efficiency and pf >0,9.

Operating Temperature Range 0 °C/+35 °C

Options

- * 1 or 3 hours emergency lighting kit
- * Dimming via DALI



Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Cut-out Size (mm)
DGMON+. 200.13.30	13	3000	1570	>80	220 - 240 / 50 - 60	0,8	Ø175
DGMON+. 200.13.40	13	4000	1690	>80	220 - 240 / 50 - 60	0,8	Ø175
DGMON+. 200.17.30	17	3000	2180	>80	220 - 240 / 50 - 60	0,8	Ø175
DGMON+. 200.17.40	17	4000	2330	>80	220 - 240 / 50 - 60	0,8	Ø175
DGMON+. 200.24.30	24	3000	2890	>80	220 - 240 / 50 - 60	0,8	Ø175
DGMON+. 200.24.40	24	4000	3140	>80	220 - 240 / 50 - 60	0,8	Ø175

