



DS 1009 SPA



Installation Installation on three-phase track.

Housing

Aluminum injection frame with electrostatic powder coating and die-cast aluminum heatsink.

Optics

Anodized aluminum reflector, designed specially for LED modules.

Led

High-efficacy COB LED with CRI>80, achieving L70B50 ≥ 50,000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and pf >0,9.

Ambient Temperature 0 °C /+25 °C

Options

Dimming via Dali



Ral 9016 Ral 9005

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle	Color
DSSPA. 09.16.40.16.90.S	16	4000	1790	>90	220 - 240 / 50 - 60	0,7	16°	Siyah(Black)
DSSPA. 09.16.40.24.90.S	16	4000	1700	>90	220 - 240 / 50 - 60	0,7	24°	Siyah(Black)
DSSPA. 09.16.40.38.90.S	16	4000	1710	>90	220 - 240 / 50 - 60	0,7	38°	Siyah(Black)
DSSPA. 09.25.40.16.90.S	25	4000	2575	>90	220 - 240 / 50 - 60	0,7	16°	Siyah(Black)
DSSPA. 09.25.40.25.90.S	25	4000	2650	>90	220 - 240 / 50 - 60	0,7	24°	Siyah(Black)
DSSPA. 09.25.40.38.90.S	25	4000	2670	>90	220 - 240 / 50 - 60	0,7	38°	Siyah(Black)
DSSPA. 09.16.40.16.90.B	16	4000	1959	>90	220 - 240 / 50 - 60	0,7	16°	Siyah(Black)
DSSPA. 09.16.40.24.90.B	16	4000	1987	>90	220 - 240 / 50 - 60	0,7	24°	Siyah(Black)
DSSPA. 09.16.40.38.90.B	16	4000	1996	>90	220 - 240 / 50 - 60	0,7	38°	Siyah(Black)
DSSPA. 09.25.40.16.90.B	25	4000	2801	>90	220 - 240 / 50 - 60	0,7	16°	Siyah(Black)
DSSPA. 09.25.40.24.90.B	25	4000	2910	>90	220 - 240 / 50 - 60	0,7	24°	Siyah(Black)

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle	Color
DSSPA. 09.25.40.38.90.B	25	4000	2903	>90	220 - 240 / 50 - 60	0,7	38°	

