



# SD 6060 OPL



## Housing

Sheet steel body with electrostatic powder coating.

## Optics

Opal white polystyrene diffuser with lambertian light distribution.

## Led

High-efficacy LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

## Driver

Constant current output LED driver with high efficiency and  $Pf \geq 0.95$

**Options\*** 1 or 3 hours emergency lighting kit

\* Dimming via DALI



Ral 9016 Ral 9006

| Type Code        | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz                | Weight (Kg) |
|------------------|-----------|---------|-------------------|-----|---------------------|-------------|
| SDOPL.6060.28.30 | 28        | 3000    | 2650              | >80 | 220 - 240 / 50 - 60 | 5,2         |
| SDOPL.6060.28.40 | 28        | 4000    | 2820              | >80 | 220 - 240 / 50 - 60 | 5,2         |
| SDOPL.6060.36.30 | 36        | 3000    | 3440              | >80 | 220 - 240 / 50 - 60 | 5,2         |
| SDOPL.6060.36.40 | 36        | 4000    | 3620              | >80 | 220 - 240 / 50 - 60 | 5,2         |
| SDOPL.6060.42.30 | 42        | 3000    | 3950              | >80 | 220 - 240 / 50 - 60 | 5,2         |
| SDOPL.6060.42.40 | 42        | 4000    | 4230              | >80 | 220 - 240 / 50 - 60 | 5,2         |

