



# S 0500 HWK - Medium



## Housing

Electrostatic powder coated aluminium injection and air pressure balancer (ventile).

## Optics

Anodized aluminum reflector specially designed in three types as narrow, medium and wide angle.

## Led

High-efficacy COB LED with CRI>80, achieving L90B50  $\geq$  50,000 hours of lifetime.

## Driver

Highly efficient with constant current output.

## Glass

Clear tempered glass

## Gasket

TPE (500600S)

## Ambient Temperature

85W / 126W : -40 °C/+40 °C

167W : -40 °C/30 °C

## Options

Dimming via DALI

## Mounting Accessory

Choose accessories according to the product mounting type.

| Type Code             | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz                | Weight (Kg) |
|-----------------------|-----------|---------|-------------------|-----|---------------------|-------------|
| SHWK.500.087.M.<br>40 | 87        | 4000    | 12180             | >80 | 220 - 240 / 50 - 60 | 7,3         |
| SHWK.500.126.M.<br>40 | 126       | 4000    | 18150             | >80 | 220 - 240 / 50 - 60 | 7,3         |
| SHWK.500.167.M.<br>40 | 167       | 4000    | 23980             | >80 | 220 - 240 / 50 - 60 | 7,3         |



