

Fry 70



The Fry range is a basic and cost-efficient range of fixed LED downlights. The Fry 70 series covers the output range of 1200lm, 2000lm and 3000lm, all available in spot, medium and flood beam, in 3 colour temperatures, with a fixed output driver or a DALI driver and in 3 different finishes: white, grey or black. A larger sized variant, Fry 111, covers the 5000lm output range.

DESCRIPTION

Recessed non-directional LED series, developed as a budget friendly and efficient solution. All versions cooled with a passive heatsink.

LED INFO

Cree COB modules integrated, ensuring a great performance and high system efficacy.

RANGE

Fry comes in two sizes and in a black, white and grey finish. Light distribution in spot, medium and flood beam in 2700K, 3000K and 4000K. All available in either CRI80 or CRI90. Output range 1200 to 5000 lumen all in fixed output or with a DALI driver.

POWER SUPPLY

230V (LED driver included)

INSTALLATION

Installation in open or ventilated ceilings. Installation in round cut-out hole with torsion springs.

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz |
|---------------|-----------|---------|-------------------|-----|---------------------|
| KOD EKLENECEK | 8 | 2700 | 970 | >80 | 220 - 240 / 50 - 60 |