



# S 0415 FEX Outdoor



## Housing

Chromate coating, electrostatic powder coated aluminium injection housing.

## Optics

Special desing clear polycarbonate optic lens to transparent glass microprism deglaring lens and tempered clear glass.

## LED

L90B50>50000 hours rated useful lifetime, hightefficacy and color rendering index.

## Driver

Highly efficient with constant current output.

## Certificate

II 3G Ex nR IIC T6...T5 Gc  
II 3D Ex tc IIIC T85°C...T 100°C Dc

## Options

Dimming via DALI

## Operating Temperature Range

-25°C/+40°C

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle	lm/W
FEX.OUT. 415.105.M1.40	105	4000	15630	80	220 - 240 / 50 - 60	9,1	66°	148
FEX.OUT. 415.150.M1.40	150	4000	21300	80	220 - 240 / 50 - 60	9,1	66°	142
FEX.OUT. 415.180.M1.40	180	4000	25240	80	220 - 240 / 50 - 60	9,1	66°	140
FEX.OUT. 415.105.M2.40	105	4000	15630	80	220 - 240 / 50 - 60	9,1	66°	148
FEX.OUT. 415.150.M2.40	150	4000	21300	80	220 - 240 / 50 - 60	9,1	66°	142
FEX.OUT. 415.180.M2.40	180	4000	25240	80	220 - 240 / 50 - 60	9,1	66°	140
FEX.OUT. 415.105.M3.40	105	4000	15630	80	220 - 240 / 50 - 60	9,1	66°	148
FEX.OUT. 415.150.M3.40	150	4000	21300	80	220 - 240 / 50 - 60	9,1	66°	142
FEX.OUT. 415.180.M3.40	180	4000	25240	80	220 - 240 / 50 - 60	9,1	66°	140

