



Stella Deboss-S / Opal



Housing

Aluminum extrusion profile and steel mounting accessories

Diffuser

Opal diffusing polycarbonate lens with lambertian light distribution

LED

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime

Driver

Constant current output LED driver with high efficiency and Pf≥0.90

Operating Temperature Range

0 °C/+35 °C

Option

Dimming via DALI

LL Low Lumen

ML Medium Lumen

HL High Lumen

- Start modules cannot be used as single. At least one piece Cont/End module is required.

* Matte natural anodized housing, finishing G90 custom color.



Ral 9016 Ral 9005 *Andz.

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Cut-out Size (mm)	L (mm)	L1 (mm)	Lumen Variations
GSSTD.1141.16.40	16	4000	1490	80	220 - 240 / 50 - 60	1130x60	1141	1127	LL
GSSTD.1141.16.30	16	3000	1400	80	220 - 240 / 50 - 60	1130x60	1141	1127	LL
GSSTD.1141.31.40	31	4000	2980	80	220 - 240 / 50 - 60	1130x60	1141	1127	ML
GSSTD.1141.31.30	31	3000	2830	80	220 - 240 / 50 - 60	1130x60	1141	1127	ML
GSSTD.1141.51.40	51	4000	4900	80	220 - 240 / 50 - 60	1130x60	1141	1127	HL
GSSTD.1141.51.30	51	3000	4650	80	220 - 240 / 50 - 60	1130x60	1141	1127	HL
GSRSTD.6158.16.40	16	4000	1490	80	220 - 240 / 50 - 60				LL
GSRSTD.6158.16.30	16	3000	1400	80	220 - 240 / 50 - 60				LL
GSRSTD.6158.31.40	31	4000	2980	80	220 - 240 / 50 - 60				ML
GSRSTD.6158.31.30	31	3000	2830	80	220 - 240 / 50 - 60				ML

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Cut-out Size (mm)	L (mm)	L1 (mm)	Lumen Variations
GSRSTD. 6158.51.40	51	4000	4900	80	220 - 240 / 50 - 60				HL
GSRSTD. 6158.51.30	51	3000	4650	80	220 - 240 / 50 - 60				HL
GSLSTD. 6158.16.40	16	4000	1490	80	220 - 240 / 50 - 60				LL
GSLSTD. 6158.16.30	16	3000	1400	80	220 - 240 / 50 - 60				LL
GSLSTD. 6158.31.40	31	4000	2980	80	220 - 240 / 50 - 60				ML
GSLSTD. 6158.31.30	31	3000	2830	80	220 - 240 / 50 - 60				ML
GSLSTD. 6158.51.40	51	4000	4900	80	220 - 240 / 50 - 60				HL
GSLSTD. 6158.51.30	51	3000	4650	80	220 - 240 / 50 - 60				HL

